

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Water Guard WG 1500
Product code : M77718

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

JR Simplot Company
Boise, ID 83707
T 1-208-336-2110

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Ox. Liq. 2 H272
Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Inhalation) H332
Skin Corr. 1A H314
Eye Dam. 1 H318

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS03

GHS05

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H272 - May intensify fire; oxidizer
H302+H332 - Harmful if swallowed or if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P220 - Keep/Store away from clothing/.../combustible materials
P221 - Take any precaution to avoid mixing with combustibles/...
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash ... thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P312 - If swallowed: Call a poison center/doctor/... if you feel unwell
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor/...
P312 - Call a poison center/doctor/... if you feel unwell
P321 - Specific treatment (see ... on this label)
P330 - Rinse mouth
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use ... to extinguish

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
sodium chlorite	(CAS No) 7758-19-2	10 - 20	Ox. Sol. 1, H271 Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Dermal), H310 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: May intensify fire; oxidizer.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: Thermal decomposition generates : Corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No naked lights. No smoking.
------------------	--------------------------------

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Take any precaution to avoid mixing with combustibles/... Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash ... thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources. Combustible materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.

Color : Cloudy

Odor : characteristic

Odor threshold : No data available

pH : < 12

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: 1.14
Solubility	: Complete. Water: Solubility in water of component(s) of the mixture : • : 39 g/100ml
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: May intensify fire; oxidizer.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. May intensify fire; oxidizer.

10.3. Possibility of hazardous reactions

May react with incompatible materials.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Overheating. Open flame.

10.5. Incompatible materials

Alkalis. metals. reducing agents. Strong acids. organic material. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Not classified. Harmful if inhaled.

Water Guard WG 1500	
ATE US (oral)	500.00000000 mg/kg body weight
ATE US (gases)	4500.00000000 ppmV/4h
ATE US (vapors)	11.00000000 mg/l/4h
ATE US (dust, mist)	1.50000000 mg/l/4h
sodium chlorite (7758-19-2)	
LD50 oral rat	390 mg/kg body weight (Aqueous solution; Rat; Other; Experimental value)
LD50 dermal rabbit	134 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	390.00000000 mg/kg body weight
ATE US (dermal)	134.00000000 mg/kg body weight
ATE US (gases)	4500.00000000 ppmV/4h
ATE US (vapors)	11.00000000 mg/l/4h
ATE US (dust, mist)	1.50000000 mg/l/4h

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: < 12
Serious eye damage/irritation	: Causes serious eye damage. pH: < 12
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

sodium chlorite (7758-19-2)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

sodium chlorite (7758-19-2)

LC50 fish 1	100 - 500 mg/l (96 h; Brachydanio rerio; Technical product)
EC50 Daphnia 1	1 mg/l (48 h; Daphnia magna; Technical product)
LC50 fish 2	50 mg/l (48 h; Lepomis macrochirus)
EC50 Daphnia 2	0.29 mg/l (48 h; Daphnia magna)

12.2. Persistence and degradability

Water Guard WG 1500

Persistence and degradability	Not established.
-------------------------------	------------------

sodium chlorite (7758-19-2)

Persistence and degradability	Biodegradability: not applicable. Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Water Guard WG 1500

Bioaccumulative potential	Not established.
---------------------------	------------------

sodium chlorite (7758-19-2)

Log Pow	-7.18 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to ...
- Additional information : Hazardous waste due to potential risk of explosion.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1908 Chlorite solution, 8, II
- UN-No.(DOT) : 1908
- DOT NA no. : UN1908
- DOT Proper Shipping Name : Chlorite solution
- Department of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136
- Hazard labels (DOT) : 8 - Corrosive



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging.
A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging.
A7 - Steel packaging must be corrosion-resistant or have protection against corrosion.
B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: t_r is the maximum mean bulk temperature during transport, t_f is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (t_f) and the maximum mean bulk temperature during transportation (t_r) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d_{15} and d_{50} are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
TP24 - The portable tank may be fitted with a device to prevent the build up of excess pressure due to the slow decomposition of the hazardous material being transported. The device must be in the vapor space when the tank is filled under maximum filling conditions. This device must also prevent an unacceptable amount of leakage of liquid in the case of overturning.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 154
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- DOT Vessel Stowage Other : 26 - Stow "away from" acids, 44 - Stow "away from" oxidizers, 89 - Segregation same as for oxidizers, 100 - Stow "away from" flammable solids

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional information

Other information : No supplementary information available.

ADR

Transport document description :

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

sodium chlorite (7758-19-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information :
: None.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal) Category 2
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Ox. Liq. 2	Oxidizing liquids Category 2
Ox. Sol. 1	Oxidizing solids Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
H271	May cause fire or explosion; strong oxidizer
H272	May intensify fire; oxidizer
H302	Harmful if swallowed
H310	Fatal in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

Water Guard WG 1500

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H332	Harmful if inhaled
------	--------------------

SDS US (GHS HazCom 2012)

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.