

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU
Product code : M80024

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

JR Simplot Company
P.O. Box 70013
Boise, ID 83707
T 1-208-336-2110

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious eye damage/eye irritation, Category 2B H320 Causes eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labelling

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H320 - Causes eye irritation
Precautionary statements (GHS-US) : P264 - Wash hands, forearms and face thoroughly after handling
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical attention

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
ammonium sulfate (7783-20-2)	(CAS No) 7783-20-2		Not classified
urea (57-13-6)	(CAS No) 57-13-6		Eye Irrit. 2B, H320
potassium chloride	(CAS No) 7447-40-7		Not classified
Monoammonium Phosphate	(CAS No) 7722-76-1		Eye Irrit. 2B, H320 STOT SE 3, H335
Polymer Coating			Not classified
wax (paraffins- petroleum)	(CAS No) 64771-72-8		Not classified

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Recover mechanically the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

urea (57-13-6) (57-13-6)

Not applicable

ammonium sulfate (7783-20-2) (7783-20-2)

Not applicable

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Monoammonium Phosphate (7722-76-1)
Not applicable
potassium chloride (7447-40-7)
Not applicable
Polymer Coating
Not applicable
wax (paraffins- petroleum) (64771-72-8)
Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless-white Unpurified: grey-brown Colourless to white Commercial substance: grey-green White Colourless
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Odourless In moist air: Ammonia odour Mild odour Petroleum-like odour
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: Not applicable
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive limits	: Not applicable
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

urea (57-13-6) (57-13-6)	
LD50 oral rat	8471 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 14300 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3200 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 21000 mg/kg (Rabbit; Literature study)
ATE US (oral)	8471 mg/kg bodyweight

ammonium sulfate (7783-20-2) (7783-20-2)	
LD50 oral rat	2840 mg/kg (Rat)
LD50 dermal rat	> 2000 mg/kg
ATE US (oral)	2840 mg/kg bodyweight

Monoammonium Phosphate (7722-76-1)	
LD50 oral rat	5750 mg/kg (Rat)
LD50 dermal rat	> mg/kg
LD50 dermal rabbit	> 7940 mg/kg (Rabbit)
ATE US (oral)	5750 mg/kg bodyweight

potassium chloride (7447-40-7)	
LD50 oral rat	2600 mg/kg (Rat)
ATE US (oral)	2600 mg/kg bodyweight

wax (paraffins- petroleum) (64771-72-8)	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity : Not classified

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

urea (57-13-6) (57-13-6)	
LC50 fish 1	> 6810 mg/l (96 h; <i>Leuciscus idus</i> ; Nominal concentration)
EC50 Daphnia 1	> 10000 mg/l (48 h; <i>Daphnia magna</i> ; Nominal concentration)
LC50 fish 2	17500 mg/l (96 h; <i>Poecilia reticulata</i>)
EC50 Daphnia 2	> 10000 mg/l (24 h; <i>Daphnia magna</i>)
TLM fish 1	17500 ppm (96 h; <i>Poecilia reticulata</i>)
Threshold limit other aquatic organisms 1	120000 mg/l (16 h; Bacteria; Toxicity test)
Threshold limit other aquatic organisms 2	> 10000 mg/l (<i>Pseudomonas putida</i>)
Threshold limit algae 1	> 10000 mg/l (168 h; <i>Scenedesmus quadricauda</i> ; Growth rate)
Threshold limit algae 2	47 mg/l (192 h; <i>Microcystis aeruginosa</i> ; Growth rate)

ammonium sulfate (7783-20-2) (7783-20-2)	
LC50 fish 1	126 mg/l (96 h; <i>Poecilia reticulata</i>)
EC50 Daphnia 1	202 mg/l (96 h; <i>Daphnia magna</i>)
LC50 fish 2	250 - 480 mg/l (96 h; <i>Brachydanio rerio</i>)
EC50 Daphnia 2	433 mg/l (50 h; <i>Daphnia magna</i>)
TLM fish 1	1290 ppm (96 h; <i>Gambusia affinis</i>)

Monoammonium Phosphate (7722-76-1)	
LC50 fish 1	155 ppm (96 h; <i>Pimephales promelas</i>)

potassium chloride (7447-40-7)	
LC50 fish 1	920 mg/l (96 h; <i>Gambusia affinis</i> ; Static system)
EC50 Daphnia 1	630 mg/l (48 h; <i>Ceriodaphnia dubia</i>)
LC50 fish 2	2010 mg/l (96 h; <i>Lepomis macrochirus</i> ; Static system)
EC50 Daphnia 2	660 mg/l (48 h; <i>Daphnia magna</i>)
Threshold limit algae 1	850 mg/l (72 h; <i>Scenedesmus subspicatus</i>)
Threshold limit algae 2	> 100 mg/l (72 h; <i>Scenedesmus subspicatus</i> ; GLP)

12.2. Persistence and degradability

urea (57-13-6) (57-13-6)	
Persistence and degradability	Inherently biodegradable. Hydrolysis in water. Not established.
ThOD	0.27 g O ₂ /g substance

ammonium sulfate (7783-20-2) (7783-20-2)	
Persistence and degradability	Biodegradability in water: no data available. Not established.

Monoammonium Phosphate (7722-76-1)	
Persistence and degradability	Biodegradability in water: no data available. Not established.

potassium chloride (7447-40-7)	
Persistence and degradability	Biodegradability: not applicable. Not established.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

wax (paraffins- petroleum) (64771-72-8)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

urea (57-13-6) (57-13-6)	
BCF fish 1	1 (72 h; Brachydanio rerio; Fresh water)
BCF other aquatic organisms 1	11700 (Chlorella sp.)
Log Pow	< -1.73 (Experimental value; EU Method A.8: Partition Coefficient)
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

ammonium sulfate (7783-20-2) (7783-20-2)	
Log Pow	-5.1
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

Monoammonium Phosphate (7722-76-1)	
Bioaccumulative potential	Not bioaccumulative. Not established.

potassium chloride (7447-40-7)	
Log Pow	-0.46 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

wax (paraffins- petroleum) (64771-72-8)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

TDG

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Polymer Coating	CAS No	%
-----------------	--------	---

Simplot Slow-Pro 28-3-5 Slow Release (N) from PCU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

wax (paraffins- petroleum)	CAS No 64771-72-8	%
----------------------------	-------------------	---

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-statements:

H320	Causes eye irritation
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.